

PAS-420

APPLICATION

BENEFITS

Hoppers/Silo Bottoms

Prevents plugging and aids material discharge

Ductwork

Prevents contamination during product changeover
Maintains material flow

Filters/Cyclones

Prevents high pressure drop
Increases bag life
Eliminates Build up

Silos/Bins

Prevents build up on vertical walls
Prevents ratholing and bridging

Dryers/Coolers/Mixers

Successful in securing complete evacuation
Eliminates bridging

and many more!

Specification:

- Frequency 420 Hz
- Sound Pressure Level 150 dB
- Air Pressure Requirement
4.8 – 6.2 bar 70 – 90 psi 480 – 620 kPa
- Air Consumption
1130 – 2260 l/min 40-80 SCFM **when sounding**
- Solid Piping 25 mm/1 inch
- Flexible Piping 20 mm/0.75 inch
- Overall height 365 mm

Material of Construction:

Bell Section	Spun 316 Grade Stainless Steel
Wave Generator	Solid Machined Stainless Steel
Diaphragm	Ultra High Grade Titanium

Accessory Equipment:

- **Solenoid Valve**
- **Individual Timer**
- **Automatic Timing System (PLC)**
- **Mounting Tube**
- **Mounting Flange**
- **Pressure Gauge/Regulator**

PRIMASONICS® INTERNATIONAL LIMITED

Technology Centre Gilwilly Estate, Penrith, Cumbria, CA11 9BD, UK.

Tel: 44 (0) 1768 866648 Fax: 44 (0) 1768 867355

Email: sound@primasonics.com Website: www.primasonics.com

t
e
c
h
n
i
c
a
l